



JCFES > 22009/22010

工作电压范围 Operating voltage range: DC(9.0~16.5)V

工作电压 Operating Voltage: DC 12.0V

工作电流 Running Current: $I_{nom} \leq 600\text{mA}$

拘束电流 Stall Current: $I_{slip} \leq 1700\text{mA}$

运行时间 Running Time: $\geq 18^\circ \text{ s}$

工作温度范围 Operating Temperature Range: $(-40 \sim 80)^\circ\text{C}$

工作耐久性 Life Endurance: $23^\circ\text{C} \pm 2^\circ\text{C}$, 10000 cycles

$80^\circ\text{C} \pm 2^\circ\text{C}$, 2500 cycles

$-40^\circ\text{C} \pm 2^\circ\text{C}$, 2500 cycles

$60^\circ\text{C} \pm 2^\circ\text{C}$, 90%RH 1000 cycles

手动调节力矩 Manual Torque: Folding torque(4.0~14.0) N · m

Opening torque(6.0~14.0) N · m

电动调节力矩 Electric Torque: 1.0~6.0 N · m

调整角度 Travel Angle: Outside folding angle: $\leq 105^\circ$

Inside folding angle: $\leq 85^\circ$

噪音水平 Sound Level: $< 65\text{dB(A)}$

Distance=500mm

承载重量 Load Capacity: 900g