



## JCFES > 22015/22016

工作电压范围 Operating voltage range: DC ( 9.0~16.5 ) V

工作电压 Operating Voltage: DC 12.0V

工作电流 Running Current:  $I_{nom} \leq 400\text{mA}$

拘束电流 Stall Current:  $I_{slip} < 1500\text{mA}$

运行时间 Running Time:  $> 18^\circ \text{ s}$

工作温度范围 Operating Temperature Range:  $(-40\sim 80)^\circ\text{C}$

工作耐久性 Life Endurance:  $23^\circ\text{C} \pm 2^\circ\text{C}$ , 10000 cycles

$80^\circ\text{C} \pm 2^\circ\text{C}$ , 2500 cycles

$-40^\circ\text{C} \pm 2^\circ\text{C}$ , 2500 cycles

$40^\circ\text{C} \pm 2^\circ\text{C}$ , 98%RH 2000 cycles

手动调节力矩 Manual Torque: Folding torque(5.0~8.0) N · m

Opening torque(7.0~12.0) N · m

电动调节力矩 Electric Torque:  $1.5\sim 6.0 \text{ N} \cdot \text{m}$

调整角度 Travel Angle: Outside folding angle:  $> 75^\circ$

Inside folding angle:  $> 55^\circ$

噪音水平 Sound Level:  $< 65(\text{monomer} < 55)\text{dB(A)}$

Distance=500mm

承载重量 Load Capacity: 900g